



# Uni-Dust Type 60

## Technical Overview

The Uni-Dust Type 60 cyclone is designed to accommodate an airflow of 800 – 1200 m3/hr (470 – 700 CFM).

The outlet catchpot can be customised to suit application product loss, typically to hold a capacity of 3 – 50 litres.

As standard, all contact parts are manufactured from 316L stainless steel (180 grit), with FDA compliant seals, gaskets etc. Non-contact parts such as portable trolleys and wall brackets are manufactured from 304 stainless steel (150 grit).

## Key Information

- > High efficiency design capturing 90 - 99.9% of powder
- > Prevents blinding and replacement of expensive filters in central dust extraction system or vacuum cleaner
- > Improved bath reconciliation and yields
- > Almost zero maintenance costs with no moving parts or filters
- > Recovered powder can be reintroduced - minimising material loss and saving money
- > GMP design
- > Suitable for use in ATEX Zone 0/20

## Data Table

Criteria	Unit	Uni-Dust Type 60
Airflow Range	m3/hr	800 – 1200
	CFM	470 – 700
Cyclone Body Dia.	mm	304.8
	in	12" T/C
Inlet / Outlet Pipe Dia.	mm	139.7
	in	5½" T/C
Product Discharge Dia.	mm	203.2
	in	8" T/C
Approximate Weight	kgs	68
	lbs	150
Typical Noise Level	dB	0 (no moving parts / no mechanical noise generated)
Contact Parts		AISI 316L stainless steel (1.4404)
Non-Contact Parts		AISI 304 stainless steel (1.4301)

## Product Images

