



## Silicone Dust Caps & Connector Sleeves

Flexible silicone accessories providing quick and cost-effective containment or transfer of powders; designed for sanitary applications in the pharmaceutical food and related industries.



# Silicone Dust Caps

## Technical Overview

The Hanningfield Uni-Cap is a flexible silicone rubber seal which provides a cost-effective method for the dust-tight transfer or containment of powders.

Compatible with our range of stainless steel mounting rings, the Uni-Cap is easily fitted or retrofitted to any process.

The Uni-Cap+ is a superior range of fully transparent silicone dust caps offering excellent process visibility. Made from platinum cured silicone, the Uni-Cap+ is classified as USP Class VI, TSE/BSE free, ADI free and phthalates free.

## Product Images



## Data Table

	Size	Diameter		Height mm	Wall Thickness mm	Material Hardness shore	Part Number	Specification
		mm	In					
Uni-Cap	2.5"	60	2.5	33	8	60	HPN005302	<b>Material</b> > Silicone  <b>Compliance</b> > FDA 21 CFR 117.2600  <b>Features</b> > Translucent
	5"	127	5	35	10	60	HPN005304	
	8"	200	8	40	10	60	HPN005306	
	10"	250	10	36	10	60	HPN005311	
	12"	315	12	32	9.5	60	HPN005314	
	16"	400	16	32	9.5	60	HPN005317	
Uni-Cap+	6 T/C	152.4	6	32	12	70, A	HPN026941	<b>Material</b> > Silicone (Platinum Cured)  <b>Compliance</b> > FDA 21 CFR 117.2600 > USP Class VI  <b>Features</b> > Translucent > Optional Batch ID
	8 T/C	203.2	8	32	10	70, A	HPN030172	
	305mm	305	12	32	11	70, A	HPN025132	
	460mm	460	18.1	32	10.5	70, A	HPN025126	



# Silicone Connector Sleeves

## Technical Overview

The Hanningfield Uni-Connect range of silicone compensator sleeves are designed to provide quick and hygienic connection for dust tight powder transfer between interfaces, which can easily compensate for misalignment between process machines.

Available in 2", 4", 6", 8", 10" and 12", the Uni-Connect is designed to be compatible with a standard Tri-Clover profile.

## Product Images



## Data Table

Criteria	Unit	2"	4"	6"	8"	10"	12"
Diameter	in	2"	4"	6"	8"	10"	12"
Length	mm	40mm	40mm	50mm	50mm	60mm	70mm
Wall Thickness	mm	1.6mm	2.4mm	2.0mm	2.0mm	2.0mm	2.0mm
Material Hardness	shore	70	70	70	70	70	70
Operating Pressure	barg	0.8	0.8	0.8	0.5	0.5	0.5
	psi	11.6	11.6	11.6	7.25	7.25	7.25
Max Pressure	barg	4.0	2.5	2.5	1.0	1.0	1.0
	psi	58	3.6	3.6	14.5	14.5	14.5
Operating Vacuum	barg	0.5	0.5	0.5	0.5	0.5	0.5
	psi	7.25	7.25	7.25	7.25	7.25	7.25
Min. Operating Temperature	°C	-20°C					
	°F	-50°F					
Max. Operating Temperature	°C	+140°C					
	°F	+289°F					
Part Number		HPN017208	HPN007324	HPN007323	HPN007321	HPN007327	HPN007325
Standard Material		Translucent Silicone (FDA CFR 177.2600)					



**UK and Worldwide  
(Headquarters)**

Hanningfield Process Systems Ltd  
17 Millhead Way  
Purdeys Industrial Estate  
Rochford, Essex, SS4 1LB  
United Kingdom

**Tel:** +44 (0) 1702 549 777

**E-Mail:** sales@hanningfield.com

**USA, Canada, Mexico  
and North America**

Hanningfield (North America) LLC  
PO Box 1107  
Fuquay-Varina  
North Carolina  
27526  
United States of America

**Tel:** +1 (919) 338 2884

**E-Mail:**  
northamerica@hanningfield.com

**Australasia and  
the Asia-Pacific**

Hanningfield (Asia-Pacific) Pty Ltd  
PO Box 362  
Kenmore  
Queensland  
4069  
Australia

**Tel:** +61 (0) 488 242158

**E-Mail:**  
pacific@hanningfield.com

**India and the  
SAARC Region**

Hanningfield India Pvt Ltd  
157/158A Akbar Camp Road  
Sandoz Baug, Kolshet  
Thane (West) 400 607  
Maharashtra  
India

**Tel:** +91 22 2586 8059

**E-Mail:**  
india@hanningfield.com